



MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS 1997 A

AUTOMATED POLYMER DIE ATTACH MACHINE

HUGHES AIRCRAFT COMPANY **TUCSON MANUFACTURING DIVISION** AD-A152

HUGHES

hughes aircraft company



Prepared for:

U.S. Army Missile Command System Engineering Directorate

ATTN: DRMSI-RHS

Redstone Arsenal, 35898

Report DAAH01-81-D-A001

AUTOMATED POLYMER DIE ATTACH MACHINE

G. M. Coppus/G. N. Hunter Hughes Aircraft Company Tucson Manufacturing Division P. O. Box 11337 Tucson, AZ 85734

13 January 1981

Initial Report

Prepared for:

U. S. Army Missile Command System Engineering Directorate ATTN: DRMSI-RHS Redstone Arsenal, AL 35898 Accession For

NTIS GRAGI
DTIC TAR
Unconnected
Justin Service

By
Distribut

Available

Dist

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION	READ INSTRUCTIONS BEFORE COMPLETING FORM							
1. REPORT NUMBER DAAHO1-81-D-A001	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER						
4. TITLE (and Subtitle)	1-111-175 X 16	5. TYPE OF REPORT & PERIOD COVERED						
AUTOMATED POLYMER DIE ATTACH MACHINE		 Initial, 1/13/81						
		6 PERFORMING ORG. REPORT NUMBER						
7. AUTHOR(s)		8. CONTRACT OR GRANT NUMBER(s)						
G.M. Coppus/G. N. Hunter								
		DAAH01-81-D-A002						
9. PERFORMING ORGANIZATION NAME AND ADDRESS		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS						
Hughes Aircraft Company Tucson Manufacturing Division		PAN: 7RY11						
P. O. Box 11337 Tucson, AZ 85	TAN. ANTI							
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE						
U. S. Army Missile Command		13 January 1981						
System Engineering Directorate ATTN: DRSMI-RHS Redstone Arsena	1 41 35000	13. NUMBER OF PAGES						
14. MONITORING AGENCY NAME & ADDRESS(It different	from Controlling Office)	15. SECURITY CLASS. (of this report)						
		Unclassified 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE						
15. DISTRIBUTION STATEMENT (of this Report)		30/12022						
13. DISTRIBUTION STRIEMENT (OF INTS REPORT)		İ						
Approved for public release; dist	ribution unlimit	ed.						
17. DISTRIBUTION STATEMENT (of the abstract entered i	n Block 29, if different from	n Report)						
18. SUPPLEMENTARY NOTES								
		1						
,								
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)								
Automatic Die Attachment; Hybrids, Polymer Die Attachment, Die Recognition								
Systems; Robotics.								
20. ABSTRACT (Continue on reverse side it necessary and identify by block number)								
•								
The report which follows specifies the program plan, technical plan and statement of work associated with the development and construction of an								
automated polymer die attach machine for subsequent utilization in a high								
rate manufacturing environment.								
	,							
•								
· · · · · · · · · · · · · · · · · · ·								

TECHNICAL REQUIREMENT

Automated Polymer Die Attach Machine

1.0 General

reduction of operator controlled variables in an effort to reduce cost while maintaining or increasing equipment volume handling capability. An important area in which this can be accomplished is in the chip to substrate assembly operation. Existing equipment is designed for operator recognition and orientation alingment of individual semiconductor chip topographies. The purpose of this manufacturing technology program is to develop a semi-automatic chip recognition Die Bonding System. __ The system must present a video image of the die to be placed on a TV Monitor. This image shall be overlayed with an outline image of the die to show correct orientation of said die. The operator will then align this overlayed image to the real die. The machine will then pick up, orient, and place the die in correct orientation on the substrate without operator control. This system must be applicable to a future fully automatic hybrid die bonder.

- 2.0 Applicable Documents
- 2.1 MIL-STD-883
- 2.2 MIL-M-38510
- 3.0 Requirements
- 3.1 Technical Effort

The contractor shall provide the personnel, materials, equipment, and expertise required to perform the tasks hereinafter required.

3.2 Planning

The technical effort to be conducted under these requirements will be planned in terms of technical tasks and related objectives to be accomplished in the pursuit of the entire program. Each task and related objective will result in the completion of a significant portion of the total effort. The following outline describes these aforementioned tasks and objectives and a milestone chart for completion of the outlined items is included in the program plan portion of this report.

I. System Analysis

- A. Mechanical Design Mechanical requirements/capabilities specification:
 - 1. Die Pickup vacuum system
 - detection of pickup
 - pickup tools
 - 2. Pickup Arm Motion/Motor Drive
 - 3. X-Y Table Motion/Motor Drive
 - 4. Waffle Pack Tooling
 - 5. Vibratory Feeder Tooling
 - 6. Work (Substrate) Holder Tooling
 - 7. Substrate Magazine
- B. Video Augmentation Design Optical requirements/capabilities specification:
 - 1. Camera
 - 2. CCTV Monitor
 - 3. Lighting
- C. Electrical Hardware Design Circuitry requirements/capabilities specification and packaging constraints.
- D. Sofware Design Capacity requirements/capabilities specification:

NOTE: The plan for accomplishing the System Analysis and their objectives will include but not be limited to:

- Task/Objective Definition
- 2) Accuracy and Resolution Requirements
- 3) Generation of Interfacial Requirements
- II. Mechanical Design this phase shall occur subsequent to the System Analysis phase and result in implementation of all system requirements, capabilities, and constraints that are developed during the course of the Systems Analysis. The individual items to undergo design shall be identical to the line items outlined under Section I, of this outline, System Analysis but will be consolidated into:
 - A. Die Pickup/Pickup Arm
 - B. Part Presentation Tooling
 - C. X-Y Table/Workholder
 - D. Substrate Magazine

- III. Video Augmentation This phase shall also occur subsequent to the System Analysis phase and results in, again, the implementation of all systems requirements, capabilities and constraints that are developed during the course of the Systems Analysis.
- IV. Hardware/Software Design Tie in of individual components:
 - A. Hardware With respect to both hardware and software the aforementioned mechanical and video designs of individual components shall be integrated resulting in full-up subsystem

design development and associated packaging.

V. Final Design (Prototype) - in this last phase of development the previously mentioned Hardware/Software subsystems shall be packaged into a final unit concept which will be subsequently assembled into a working prototype allowing performance evaluation of the individual components and subsystems.

The plan for performance of Sections II through V identified above shall include but not be limited to:

- 1) Performance specification generation
- 2) Drawing development
- 3) Components and Materials selection
- 4) Procurement of vended components and materials.
- 3.3 Description of Effort to be Performed
 - 3.3.1 General Description

The hybrid die bonder is to be a semi-automatic computer-controlled system for attaching semiconductor die components to ceramic substrates. The dies are bonded to the substrate by utilizing pre-screened epoxy. The system will be composed of a pick and place arm, a substrate workholder with automatic substrate feed from magazines and an array of up to forty-two 2 x 2 inch waffle packs or a combination of waffle packs and linear vibratory chip feeders.

In operation, a substrate is automatically fed by the work-holder from the magazine to the bond site and clamped into position. The position of the substrate is aligned to cross-hairs on a CCTV monitor. Following pretaught instructions, the computer will direct the pick and place arm to the proper waffle pack where the next available die is displayed on the monitor. The amount of die misalignment and its orientation is determined by image correlation techniques. The die is

then picked up and placed in its proper orientation on the substrate. This cycle will continue until the substrate has been completely bonded. The substrate is then fed into the output magazine and replaced by a new one and the process continues. The computer monitors the number of die in each waffle pack or feeder and will signal via the CCTV monitor when a waffle pack must be replaced or feeder refilled. Waffle pack trays and feeders slide out from under the machine cover to allow the operator to quickly replace or refill them. When all substrates have been completed, the system automatically stops.

3.3.2 Alignment Accuracy

The chip recognition system shall be capable of positioning components within \pm .002 inches of the exact position and within \pm 5 degrees of the exact orientation.

3.3.3 Production Rates

The semi-automatic system must have a through-put of 25 or more substrates per hour with approximately 30 dies per substrate.

3.3.4 Configuration

3.3.4.1 Overall Dimensions

The system size will be approximately 48 inches wide x 36 inches deep x 50 inches high or less and will occupy floor space of approximately 48 inches wide x 48 inches deep or less.

3.3.4.2 Substrate Feed

Substrates must be fed automatically from magazines or equivalent and cycle at approximately two (2) seconds or less.

3.3.4.3 Waffle Pack Capacity

The system must accommodate approximately forty-two (42) 2 x 2 inch waffle packs (Flourware type or equivalent) from which die may be selected.

3.3.4.4 Vibratory Chip Feeder

The system must provide for up to eight chip feeders. The maximum number of waffle packs (3.3.4.3) may be reduced to thirty-six (36) if eight feeders are configured.

3.3.5 Other Requirements

The system shall not subject the substrate to temperatures in excess of 100°F. The system shall not damage devices being attached to substrates. The system shall have an emergency stop capability.

4.0 Documentation

- The contractor shall prepare a final report detailing the investigations, tests, and data collected during the course of this project. Data to be delivered, schedule of delivery, and distribution requirements are specified on DD Form 1423. The final report shall contain an outline of the work performed, a general description of the developed manufacturing equipment (with references), a technical description of the process; and shall contain all the material, either within the reports or within the references required to duplicate the equipment and technology. Other reports required shall be as listed on DD Form 1423.
- The contractor shall propose, to the Government, an implementation plan which details the steps to be taken by the contractor to implement the results of this effort. The implementation plan shall cover those facilities owned and/or operated by the contractor and those subcontracted facilities participating in this contract. The primary emphasis of the implementation plan shall be Army Missile Systems and end items/components of Army Missile Systems currently under development or production by the contractor. Data as to the applicability of this project's results to Air Force and/or Navy development/production efforts is also of importance and shall be addressed in the implementation plan.
- 4.3 The contractor shall provide a 10 minute narrated video tape, and a set of fifty (50) 35mm color slides depicting the manufacturing process, suitable as a familiarization and instructional tool. The determination on the exact content and method shall be by the contractor with Government approval. Delivery shall be at the conclusion of the contract.

- 4.4 The contractor shall orally review the progress of the work to the Government at quarterly intervals, at mutually agreeable times and places. Other reviews, if determined necessary by the Government, shall not exceed three (3) per year.
- The contractor shall perform an industry demonstration. The contractor shall give the Government sixty (60) days notice prior to demonstration.

Program Plan for Tasks Concerning Automated Polymer Die Attach Machine

1.0 General

This program plan identifies the work to be completed during the performance of MICOM Project #3219, "Automated Polymer Die Attach Machine". The majority of work completed shall occur at Kulicke and Soffa (K & S), equipment manufacturer, with Hughes Aircraft in an overseers capacity ultimately resulting in buy-off of system concept and prototype performance as identified in the Technical Requirements sections of this report.

2.0 Milestones

The attached chart displays the major items to be completed, the time required and the sequence of events of each.

			-					<u> </u>	فسعة			···	-	-	
HUG			D D C	VC B /	\ 4.4 T.I	716	V	лісс	OM F	PRO.	JECT	ΓNC). 32°	19	
			DESCF			16.									
						Α	UTC	AMC	TEI	O PO	LYN	1ER	DIE	ATT	
WBS L	7	LCOST ACCT, NO													
CRG SO		ACTIVITY/EVENT DESCRIPTION	-	MONTHS AFTER GO-AHEAD											
	CL OF		-	1			2		3	7	1		5	6	
	I	System Analysis		Δ						1					
		A. Nech Design Analysis		Δ							Δ				
		1. Die Pickup		\triangle						Δ					
		2. Pickup Arm			Δ						Δ				
		3. X-Y Table		\triangle						Δ					
		4. Waffle Pack Tooling			\triangle						^				
		5. Vibratory Feeder Too	oline]	\wedge						^				
		G. Workholder Tooling	1		Δ						1			_	
		7. Substrate Magazine		\triangle					Δ					1	
		B. Video Augmentation Desi	gn			Δ							Δ		
1		l. Camera				Δ		-	-		Δ			1	
1		2. CCTV Monitor					Δ					Δ			
1		3. Lighting						Δ					Δ	1	
1		C. Electrical Hdwr. Design				\triangle							Δ		
1		D. Software Design				Δ									
1	11	Mechanical Design										Δ			
1		A. Die Pickup/Pickup Arm										Δ		1	
		B. Part Presentation Tooli	ng									\triangle			
1		C. X-Y Table/Workholder										\triangle		_	
i	\prod	D. Substrate Magazine										\triangle			
1	111	Video Augmentation										\triangle			
	ΙV	Hardware/Software Design										\triangle		<u></u>	
		A. Hardware										$\overline{\wedge}$			

B. Software

Reporting

Film

V Final Design (Prototype)

ORGANIZATION	RESPONSIBILITY	PAGE	Or
CHINE	NAME	ORG CODE	EXT.
·•	CONTRACT NO.	REFERENCE NO.	PROD. LINE
SCHEDULE	1	TETETOTION .	
8 9 10 11 12			
+4			
			
1-			

PREPARED BY

OPG CODE

EST.

END

FILMED

A

4-85

DTIC